


HAVELLS
enviro
 Solar Module

ENVIRO-PVM6 / PVC-40 / 50 / 60 / 100 / 150 / 270 / 325

ENVIRO-PVM6/PVC Series consist of PV Modules with power ratings ranging from 40 Wp to 325 Wp

The high performance Poly-Crystalline Modules are designed for on-grid as well as off-grid applications.

KEY FEATURES

- Made from high efficiency crystalline silicon solar cells
- Reliable products suiting all environmental conditions
- Product warranty-upto 10 years
Power output warranty-upto 25 years

 Performance under standard test conditions
 (1000 W/m² AM1.5, 25°C)

	ENVIRO PVM6/ PVC-40	ENVIRO PVM6/ PVC-50	ENVIRO PVM6/ PVC-60	ENVIRO PVM6/ PVC-100	ENVIRO PVM6/ PVC-150	ENVIRO PVM6/ PVC-270	ENVIRO PVM6/ PVC-325
Rated power (Pmax), Wp	40	50	60	100	150	270	325
Max power voltage (Vmp), V	17.9	17.9	18.55	17.9	18.52	31.2	37.41
Max power current (Imp), A	2.32	2.8	3.25	5.7	8.26	8.68	8.69
Open circuit voltage (Voc), V	21.6	21.6	22.5	21.6	21.6	37.25	46.21
Short circuit current (Isc), A	2.52	3.1	3.45	6.3	8.6	8.55	9.18
Module efficiency (%)	13.5	13.5	13.5	14.9	15.4	16.2	16.77
Number of cells	36	36	36	36	36	60	72
Physical Parameters							
Module dimensions (mm)	472*666	545*666	666*666	1005*668	1485*668	1639*991	1957*990
Module thickness (mm)	35	35	35	35	35	35	40
Approximate weight (kg)	3.95	4.4	5.3	7.65	11.1	18.5	21.5
Operating Conditions							
Ambient temperature, °C	-40 to + 80						
Maximum system voltage, Vdc	600 V for 40 W / 50 W / 60 W / 100 W, 1000 V for 150 W / 270 W / 325 W						
Maximum surface load capacity	5400 Pa						
Characteristics							
Cell Type	Poly						
Glass	3.2 toughened textured glass						
Frame	Silver anodized aluminum alloy						
Junction Box	IP 67						

Channel Partner

Office: No.1, Thiruvalluvar Street,
 Nehru Nagar, Bypass Road,
 Madurai - 625010.
 Ph: 0452-436751
 Cell: 99445 62271

Branch: Plot No.2,
 Pasumpon Thevar Street,
 Ellis Nagar, Madurai - 625016.
 Ph: 0452 - 3590160
 Cell: 94442 66271

 E-mail : jananipowermdu@gmail.com Web : www.jananipowerengineering.com
Copyright/Subsists. Imitation of trade dress, graphics and colors scheme of this document is a punishable offence.
Havells India Ltd.
GFG Towers, 2D, Sector-126, Expressway, Noida-201304 (UP), Ph. +91-120-3331000,
 E-mail: marketing@havells.com, www.havells.com
 Consumer Care No.: 1 800 1 10003, 1800 103 1313 (All Connections), 011-41660303 (Landline)
 Join us on Facebook at www.facebook.com/havellsandshareyourwaystosaveplanet!
 CIN-L31900DL1983PLC016304.

HAVELLS